

A.S.P. Electro-Technology Ltd
INFORMATION SHEET

I.S. Conventional Rate of Rise Heat Detector – Model DCD-1E-IS

Features

- Twin fire LED's allow 360° viewing
- Electronics free mounting base
- Supported by a wide range of barriers
- Remote indicator output
- Certified by BASEEFA to II 1 G EEx ia IIC T5
Tamb=55° C
- Suitable for installation in areas at Category 1 (inc
all lower categories)



Description

The DCD-1 E-IS is an Intrinsically Safe Conventional Rate of Rise Heat Detector with a 60° fixed temperature element

Specification

Ordering Code	YBO-R/5PA
Operating Voltage	15-30V
Operating Temp. Range	-10° C to + 55° C
Storage Temp. Range	-30° C to + 70° C
Maximum Humidity	95%RH - Non Condensing (at 40° C)
Colour	Ivory White
Diameter	100mm
Height	46mm (with base)

Supplied by:

A.S.P. Electro-Technology Ltd
*Specialist Suppliers of Hazardous Area
Certified Electrical Products & Instrumentation*

39 London Road, Hinckley, LE10 1HQ. U.K.
Tel: +44 (0)1455 635796 Fax: +44 (0)1455 251110
Email: sales@asp-electro-tech.com Web: asp-electro-tech.com



This publication is not intended to form the basis of a contract. All the above specifications, dimensions, weights, tolerances etc are typical and may be varied or changed by the manufacturer without prior notice. A.S.P. Electro-Technology accept no liability for consequence of use.