

230/240 V - 50 Hz IIB floodlights, armoured and non-armoured cable flameproof



0951 79 + 0951 93



Quick access to the lamp

70 to 500/1000 W floodlights

- Compensated power supply 230/240 V ($\pm 10\%$) 50 Hz
 - Power factor ~ 0.9 (except Cat. No. 951 65)
- 24 V AC/DC power supply for Cat. No. 0951 65
- Grey painted marine grade aluminium alloy body and bezel - Toughened glass sealed onto frame
- Stainless steel fasteners
- Highly polished anodised aluminium internal reflector
- E40 lampholder (except 951 65)
- Adjustable lampholder for changing lighting from narrow to wide beam
- Increased safety terminal box
- Components: ballast, igniter, capacitor separated from the lamp housing, ensuring increased thermal insulation
- Rapid access to the lamp via threaded cover with safety chain
- Frame has reversible hinge so that it can be pivoted on both sides
- Operates in any position
- 2 self-tightening connection terminals: capacity: $2 \times 6 \text{ mm}^2$ max.
 - 2 earthing terminals capacity 6 mm^2
 - external earth 4 mm^2
- Two M20 through wiring cable entries
 - Supplied with :
 - One M20 blanking plug and two locknuts
 - One M20 cable gland for non armoured cable (sealed $\varnothing 6.5$ to 14.5 mm)

Accessories

	Cat. No.	Pack
Galvanised steel hinged bracket for Cat. No. 0951 65/66/67/68/69/73/77/79/84	0951 93	1
Set of 2 galvanised steel clamp brackets for:		
- Fixing on 1" 1/4 ($\varnothing 42 \text{ mm}$)	0951 98	1
or 1" 1/2 ($\varnothing 49 \text{ mm}$) tube	0951 90	1
- Fixing on 2" ($\varnothing 60$) tube		
Clip-on overhead diffuser (1)	0951 91	1
Clip-on protective guard (1)	0951 95	1
Set of horizontal fixings	0951 97	1
400 W mercury vapour cylindrical lamps	0948 95	1

(1) These 2 accessories cannot be fitted together

For special options, please consult us:

- 110/127 V 50/60 Hz - 208 V - 254 V, 50 Hz ...
- 2 additional terminals for 3-phase + neutral 380/415 V loop in loop out (connection possible)
- Temperature class T4

Catalogue numbers

Permissible lamps (not supplied)	Type		Weight (Kg)	Volume (dm ³)	Cat. No. 230/240 V	Pack.
	(1)	(2)				
150 W HP sodium	X	X	27.3	79.4	0951 6 6	1
250 W HP sodium	X	X	28.3	79.4	0951 6 9	1
400 W HP sodium		X	29.8	79.4	0951 7 9	1
250 W mercury vapour	X	X	27.3	79.4	0951 6 7	1
400 W mercury vapour		X	27.8	79.4	0951 7 3	1
250 W metal halide	X	X	28.3	79.4	0951 6 8	1
400 W metal halide		X	29.8	79.4	0951 7 7	1
500 W / 1000 W halogen		X	24.3	79.4	0951 8 4	1
2 x 70 W halogen H3 24 V (3)			25.3	79.4	0951 6 5	1

(1) Ovoid - (2) Tubular - (3) Lamps supplied

Distributor:

A.S.P. Electro-Technology Ltd,
39 London Road, Hinckley,
LE10 1HQ, U.K.

Tel: 01455 635796 Fax: 01455 251110

Email: Sales@asp-electro-tech.com

Web: www.asp-electro-tech.com

This publication is not intended to form the basis of a contract. All the above specifications, dimensions, weights, tolerances etc are typical and may be varied or changed by the manufacturer without prior notice. A.S.P. Electro-Technology accept no liability for consequence of use.

