

Cylindrical fluorescent luminaires 220/230 V - 60 Hz for armoured and non-armoured cable flameproof



0948 11 FLD 2 x58W



0948 10 FLD 2 x36W



0948 09 FLD 2 x18W



0948 09 with reflector 948 69 and protective guard 0948 73

18, 36 and 58 W cylindrical fluorescent luminaires

- Ferromagnetic ballast
- Ø 26 or 38 mm twin tubes, G13 lampholders
- Borosilicate glass sealed tube
- Zamak end caps and cover anticorrosion treated and painted grey
- Threaded access cover with O ring seal
- High temperature internal wiring
- Connection via 2 x 3 x 2.5 mm² terminals
- Two M20 threaded cable entries
- Supplied with an M20 blanking plug (cable gland not supplied)
- External earth via bracket : 4 mm²
- Operates in any position - Fixed using 2 integrated lugs (see accessories opposite)

For Ø 26 or 38 mm G13 fluorescent tubes

- Compensated power supply 220 V +6% - 10% , 60 Hz (power factor ~ 0.90). Starter ignition

Tube (W) (not supplied)	Group	Weight (Kg)	Volume (dm ³)	Cat. No. 220 V	Pack
2 x 18	II C	9.7	58	0948 09	1
2 x 36	II B	15.3	99	0948 10	1
2 x 58	II B	18.2	119	0948 11	1

- Compensated power supply 230 V +6% - 10% , 60 Hz (power factor ~ 0.9). Starter ignition

Tube (W) (not supplied)	Group	Weight (Kg)	Volume (dm ³)	Cat. No. 230 V	Pack
2 x 18	II C	9.7	58	0948 18	1
2 x 36	II B	15.3	99	0948 19	1
2 x 58	II B	18.2	119	0948 20	1

Accessories

Reflectors

White painted galvanized steel, guard fitted separately

0948 09/18

0948 10/19

0948 11/20

Protective guards Zinc-plated steel (20 microns), reflector fitted separately

0948 09/18

0948 10/19

0948 11/20

Fixings - set of 2 brackets

Quick fixing, zinc-plated steel

316 stainless steel version

Fixing on flat surface, zinc-plated steel

316 stainless steel version

With zinc-plated brackets for fixing on

– 1" 1/4 (Ø 42 mm) or 1" 1/2 (Ø 49 mm)

– 316 stainless steel version


– 2" (Ø 60 mm) tube


– 316 stainless steel


version Fall prevention

fixing kit (1.20 m stainless

steel chain)

	Cat. No.	Pack
	0948 69	1
	0948 70	1
	0948 71	1

	0948 73	1
	0948 74	1
	0948 75	1

	0948 97	1
	0948 89	1
	948 98 1	0
	0948 99	1
	0948 92	1
	0948 91	1
	0948 93	1
	0938 19	11

For special options, please consult us:

- 254 V + 6% - 10%
 - Version with three Ø 26 tubes
 - Tubes designed for cold applications, for increasing the flux at low temperature
 - Hinged fixing with chain
 - Three entry version
- Spare parts (see page 290)
Cable gland for armoured cable (see page 252-262)

Distributor:

A.S.P. Electro-Technology Ltd,
39 London Road, Hinckley, LE10 1HQ. U.K.
Tel: 01455 635796 Fax: 01455 251110
Email: sales@asp-electro-tech.com
Web: asp-electro-tech.com.

