



A.S.P. Electro-Technology Ltd

Tel: +44 (0) 1455 635796
 Fax: +44 (0) 1455 610851

sales@asp-electro-tech.com
 www.asp-electro-tech.com

DN Series Bulk head Luminaire

Certification and Approval

- **Certification Code**
 EEx nC II 3GD T3 (See lamp tables for T rating)
- **Certification number** 03 ATEX TFDN/01
- **Certification standard** EN 60079-0, 15
- **Protection** IP 65

Features

- Rapid lamp and control gear access
- Even light distribution
- Hinged lens opening

Options

- Lamp source variants
- Power factor correction
- Various lamp options available

Technical Data

Supply Voltage	230v 50Hz standard.	
Operating Temperature	-20°C to +30°C standard supply subject to ambient temperature requirements.	
Control Gear	Integral within the luminaire and optional power factor correction	
Lamp Options	Elliptical: 70w SON 80w HPMV 200w GLS Twin 26w PL	
Cable Entries	2 x M20 Threaded entries at one end (1 plugged).	
Terminals	<ul style="list-style-type: none"> • 2 wire and earth. • Cable size 4mm² max 	
Mounting Facility	4 cast in fixing lugs to take M8 screws.	
Access	Unscrew retaining screws to open hinged lens.	
Material	Die cast aluminium body and bezel and borosilicate glass lens	
Finish	Grey Powder coating or 2 Pack epoxy paint on primed surface. Additional costs for non standard colours.	
Weight	70w and 80w	6.0Kgs
	200w	4.0Kgs
Features	<ul style="list-style-type: none"> • Rapid lamp and control gear access • Even light distribution • Various lamp options available 	



Hinged lens opening Screwed bezel fixings Integral mounting feet

