



A.S.P. Electro-Technology Ltd

Tel: +44 (0) 1455 635796
 Fax: +44 (0) 1455 610851

sales@asp-electro-tech.com
 www.asp-electro-tech.com

'HFT' Air Sensing Thermostat

All EXHEAT Flameproof thermostats are ATEX certified Ex'd' IIC T6, suitable for installation in Zone 1 or 2 Hazardous Areas. The HFT is designed for the temperature control of work or storage areas, in conjunction with a Hazardous Area air heater.

Features

- ATEX certified Ex II 2 G IECEx & ATEX certified Ex'd' IIC T6 for Zone 1 or 2 (Gas) and GOST-R
- Wall mounted
- Stainless steel enclosure
- Suitable for ambient temperatures from -60°C to +60°C
- Ingress protection IP66



Technical Data

Certification	ATEX certified Ex II 2 G IECEx & ATEX certified Ex'd' IIC IP66 T6 for Zone 1 or 2 (Gas) and GOST-R
Enclosure	Cast Stainless Steel with two x M20 cable entries, external and internal earths and internal neutral link
Controls	Choice of control range: 0°C to 40°C or 0°C to 60°C
Mounting	2 x 6mm dia shrouded mounting holes are provided.
Voltage	SPDT, 16 Amp 250v in a choice of switching configuration

